
Technical sheet


ER 14

Warehousing Equipment



 **MANITOU**
HANDLING YOUR WORLD

Technical characteristics		Metric
1.1	Manufacturer	Manitou
1.2	Model	ER 14
1.3	Type of traction	Electric
1.4	Type of operation	Seated
1.5	Q - Rated capacity	1400 kg
1.6	c - Center of gravity of load	600 mm
1.9	y - Wheelbase	1378 mm
Weight		
2.1	Weight of truck in working order	2810 kg
2.3	Unladen weight on front/rear axle	1690 kg / 1120 kg
Wheels		
3.1	Tyre equipment: bandage (V), PPS (SE), inflatable tyre (L)	Cellular solid cushion
3.2	Size of front wheels	355 x 155
3.3	Size of rear wheels	220 x 85
3.5	Number of front wheels (x)	1x / 2
3.6	b10 - Front track	0 mm
3.7	b11 - Rear track	995 mm
Dimensions		
4.1	α / β - Front/Rear mast angle	1° / 3°
4.2	h1 - Height (mast lowered)	2440 mm
4.4	h3 - Lift height (Duplex mast)	5700 mm
4.5	h4 - Height of extended mast	6280 mm
4.7	h6 - Height of driver protection (cab)	2200 mm
4.8	h7 - Height of seat	1080 mm
4.19	l1 - Total length	2413 mm
4.20	l2 - Length to fork heel	1263 mm
4.21	Overall length - Single/twinned wheels	1120 mm / -
4.22	e / s / l - Fork dimensions	40x 100 x 1150
4.23	Fork carriage to DIN 15173 A/B	2A
4.24	b3 - Width of fork clamp	830 mm
4.31	m1 - Ground clearance under mast	70 mm
4.34	Ast - Aisle width for 800 x 1200 pallet lengthwise	2750 mm
4.35	Wa - Turning radius	1598 mm
Performances		
5.1	Speed of travel laden / unladen	12.30 km/h / 12.50 km/h
5.2	Lifting speed laden / unladen	0.49 m/s / 0.65 m/s
5.3	Lowering speed laden / unladen	0.59 m/s / 0.55 m/s
5.7	Maximum ramp laden / unladen	7.50 % / 11.10 %
5.10	Service brake	Electromagnetic
Engine		
6.1	Drive motor power rating	5.90 kW
6.2	Lift motor power	11 kW
6.4	Battery voltage/capacity	48 V / 465 Ah
Miscellaneous		
8.1	Type of drive unit	Electronic
8.2	Working hydraulic pressure for attachments	150 bar
8.3	Oil flow rate for attachments	25 l/min
8.4	Measured/guaranteed mean noise level at the ear of the operator	57.40 dB(A)



Head office
430 rue de l'Aubinière - 44150 Ancenis Cedex - France
Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,547,824 euros - 857 802 508 RCS Nantes